

KOWA OKULARE - TECHNISCHE DATEN

| Modell | auf Serie | Vergrößerung | Reelles Sichtfeld | Austrittspupille | Relative Helligkeit | Dämmerungszahl | Austrittspupillenabstand | Blickfeld / 1.000m |
|---------------|-----------|--------------|-------------------|------------------|---------------------|----------------|--------------------------|--------------------|
| TE-10Z | TSN-880 | 20~60X,Zoom | 2,2°~1,1° | 4,4~1,5mm | 19,4~2,3 | 42,0~72,7 | 17~16,5mm | 38,4~19,3m |
| TE-17W | TSN-880 | 30X,Wide | 2,4° | 2,9mm | 8,4 | 51,4 | 20mm | 41,9m |
| TE-20H | TSN-880 | 25X,LER | 2,1° | 3,5mm | 12,3 | 46,9 | 32mm | 36,7m |

| | | | | | | | | |
|---------------|---------|-------------|-----------|-----------|----------|-----------|-----------|------------|
| TE-10Z | TSN-770 | 20~60X,Zoom | 2,2°~1,1° | 3,9~1,3mm | 15,2~1,7 | 39,2~68,0 | 17~16,5mm | 38,4~19,3m |
| TE-17W | TSN-770 | 30X,Wide | 2,4° | 2,6mm | 6,8 | 48,1 | 20mm | 41,9m |
| TE-20H | TSN-770 | 25X,LER | 2,1° | 3,1mm | 9,6 | 43,9 | 32mm | 36,7m |

| | | | | | | | | |
|---------------------------|---------|-------------|-----------|-----------|----------|-----------|-----------|------------|
| TE-9Z (TSE-Z9B) | TSN-660 | 20~60X,Zoom | 1,9°~1,0° | 3,3~1,1mm | 10,9~1,2 | 36,3~62,9 | 16,5~16mm | 33,2~17,5m |
| TE-6Z (TSE-Z6) | TSN-660 | 20~40X,Zoom | 1,9°~1,4° | 3,3~1,7mm | 10,9~2,9 | 36,3~51,4 | 18,5~15mm | 33,2~24,4m |
| TE-21WD (TSE-21WD) | TSN-660 | 20X,Wide | 3,3° | 3,3mm | 10,9 | 36,3 | 20mm | 57,8m |
| TE-14WD (TSE-14WD) | TSN-660 | 30X,Wide | 2,4° | 2,2mm | 4,8 | 44,5 | 20mm | 41,9m |
| TE-9WD (TSE-9WD) | TSN-660 | 45X,Wide | 1,43° | 1,5mm | 2,3 | 54,5 | 15mm | 25,0m |
| TE-17HD (TSE-17HD) | TSN-660 | 25X,LER | 2,1° | 2,6mm | 6,8 | 40,6 | 32mm | 36,7m |

| | | | | | | | | |
|---------------------------|---------|-------------|-----------|-----------|---------|-----------|-----------|------------|
| TE-9Z (TSE-Z9B) | TSN-600 | 20~60X,Zoom | 1,9°~1,0° | 3,0~1,0mm | 9,0~1,0 | 34,6~60,0 | 16,5~16mm | 33,2~17,5m |
| TE-6Z (TSE-Z6) | TSN-600 | 20~40X,Zoom | 1,9°~1,4° | 3,0~1,5mm | 9,0~2,3 | 34,6~49,0 | 18,5~15mm | 33,2~24,4m |
| TE-21WD (TSE-21WD) | TSN-600 | 20X,Wide | 3,3° | 3,0mm | 9 | 34,6 | 20mm | 57,8m |
| TE-14WD (TSE-14WD) | TSN-600 | 30X,Wide | 2,4° | 2,0mm | 4 | 42,4 | 20mm | 41,9m |
| TE-9WD (TSE-9WD) | TSN-600 | 45X,Wide | 1,43° | 1,3mm | 1,7 | 52 | 15mm | 25,0m |
| TE-17HD (TSE-17HD) | TSN-600 | 25X,LER | 2,1° | 2,4mm | 5,8 | 38,7 | 32mm | 36,7m |

| | | | | | | | | |
|--------------------------|---------------|-------------|-----------|------------|---------|-----------|---------|------------|
| Zoom* (TS-501) | TS-501 | 20~40X,Zoom | 2,3°~1,3° | 2,5~1,25mm | 6,3~1,6 | 40,5~57,3 | 14~12mm | 40,1~22,7m |
| 20X* (TS-501/502) | TS-501/TS-502 | 20X | 3,0° | 2,5mm | 6,3 | 40,5 | 13mm | 52,4 |

* Die Okulare der Spektivserie TS-500 können NICHT ausgetauscht werden